

Eye & Eye Web Sling



Type 3 EEF

Eye & eye sling, flat eyes



- Minimum breaking load is 5X WLL
- 3" and wider slings use tapered eyes as standard
- Polyester as standard, nylon available upon request
- Consider round slings in applications requiring 3-ply & 4-ply thick slings wider than 6"
- Extra protection is recommended in the eyes and on the body of the sling
- Custom slings available upon request

SYNTHETIC SLINGS

Ply	Part Number	Vertical Hitch	Choker Hitch	Vertical Basket	Web Width	Eye Length	Eye Width
		<i>Lbs</i>	<i>Lbs</i>	<i>Lbs</i>	<i>Inch</i>	<i>Inch</i>	<i>Inch</i>
One Ply	1901	1,600	1,280	3,200	1	9	1
	1902	3,100	2,480	6,200	2	9	2
	1903	4,700	3,760	9,400	3	12	1-1/2
	1904	6,200	4,960	12,400	4	14	2
	1906	9,300	7,440	18,600	6	18	2
	1908	11,800	9,440	23,600	8	22	3
	1910	14,700	11,760	29,400	10	28	3-1/2
	1912	17,600	14,080	35,200	12	30	4
Two Ply	2901	3,100	2,480	6,200	1	9	1
	2902	6,200	4,960	12,400	2	9	2
	2903	8,800	7,040	17,600	3	12	1-1/2
	2904	11,000	8,800	22,000	4	14	2
	2906	16,500	13,200	33,000	6	18	2
	2908	22,700	18,160	45,400	8	22	3
	2910	28,400	22,720	56,800	10	28	3-1/2
	2912	34,100	27,280	68,200	12	30	4
Three Ply	3901	4,700	3,760	9,400	1	12	1
	3902	9,300	7,440	18,600	2	12	2
	3903	13,500	10,800	27,000	3	14	1-1/2
	3904	17,200	13,760	34,400	4	18	2
	3906	24,400	19,520	48,800	6	24	3
	3908	30,700	24,560	61,400	8	26	4
	3910	36,000	28,800	72,000	10	30	5
	3912	40,300	32,240	80,600	12	42	6
Four Ply	4901	5,500	4,400	11,000	1	12	1
	4902	11,000	8,800	22,000	2	12	2
	4903	16,400	13,120	32,800	3	14	1-1/2
	4904	20,400	16,320	40,800	4	18	2
	4906	30,800	24,640	61,600	6	26	3
	4908	41,000	32,800	82,000	8	28	4
	4910	48,000	38,400	96,000	10	32	5
	4912	60,000	48,000	120,000	12	44	6